

**SHOPRIDER®**



**K0825**

## **6RUNNER® I4** [888WNLLHD]

The 6Runner® series powerchairs, all with 6 points of contact with the ground, provide the desired stability of traditional rear driven powerchairs, along with the maneuverability of modern mid wheel driven powerchairs. The 6Runner® series powerchairs deliver the best features available in today's powerchair technology all in one finished package.

Toll-Free: 800.743.0772  
[www.shoprider.com](http://www.shoprider.com)



Flip-up arm rest



Adjustable height

## MID WHEEL DRIVE

- Luxurious leatherette seat
- 21" high back executive seat
- Stable four post seating system
- Reclining seat and adjustable seat height
- Adjustable length, height and angle foot plate
- Adjustable width, height and flip-up arm rest
- Midwheel drive maneuverability
- 14" wheels
- 450 lb. capacity (888WNLLHD)

# 6RUNNER® 14



Red

Overall Dimensions (L x W x H)	in	43 x 26 x 49
Number, Size of Tires (front; rear)	Front (rear)	2, 7"; 2, 14"; 2,7"
Maximum User Weight (on a level road)	lb	450
Total Weight (w/battery, 50Ah*2)	lb	231
Each Battery Module Weight (75Ah)	lb	52
Battery Module Capacity (Standard)	_V_Ah x Pcs	12V50Ah x 2
Charger		Off Board (5A)
Output Power of Motor	hp	1.34 x2
Maximum Speed	mph	3.75
Max. Climbing Angle/Safe Climbing Angle(based on user weight of 90kg/200lb.)	% (°)	10 (6)
Range per charge (50Ah/75Ah) (After the battery and mechanical moving parts fully break in)	mile	18/24
Turning Radius	in	17-26

All specifications are subject to change without prior notice. Shoprider Mobility Products, Inc. reserves the rights of any changes to the unit.

1) Include the anti-tip wheel or the rear castor.

2) Driver weight may exceed weight of the unit; speed must be reduced when turning.

3) The actual driving range varies with the factors shown as below:

a) The weight of occupant

b) Ground surface

c) Battery capacity and conditions

d) Type of charger

e) Ambient temperature

f) The way of driving

g) If the battery and mechanical moving parts fully break in

h) Etc.